

Centrecoat MMA Clear Sealer Base

Page 1/8

Revision 1

Revision date 2019-10-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Centrecoat MMA Clear Sealer - Base
--------------	------------------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;
-------------	--

1.3. Details of the supplier of the safety data sheet

Company	Promain UK Limited
Address	C1 Pierson Court Knowl Piece, Hitchin Hertfordshire SG4 0TY
Web	www.promain.co.uk
Telephone	01462 421333
Fax	-
Email	info@promain.co.uk

1.4. Emergency telephone number

Emergency telephone number	01462 421333 8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri
----------------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;
--------------------------------------	---

2.2. Label elements

Hazard pictograms	 
Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Print date 2019-10-29

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

2.2. Label elements

Precautionary Statement: Response	P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
2-Ethylhexyl acrylate	607-107-00-7	103-11-7	203-080-7	01-2119453158-37		STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
N,N-bis-(2-hydroxypropyl)-p-toluidine		38668-48-3	254-075-1	01-2119980937-17		Acute Tox. 2: H300; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
-------------------	-------------------------

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

4.3. Indication of any immediate medical attention and special treatment needed

Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
--	--

5.2. Special hazards arising from the substance or mixture

	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area. Wear suitable respiratory equipment when necessary.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.
--	--

6.4. Reference to other sections

	See section 8 for further information. See section 13 for further information.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Vapours are heavier than air.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store in original container.
--	---

7.3. Specific end use(s)

	See section 1.2 for further information.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values


Methyl methacrylate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 208
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 416
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

8.2. Exposure controls



8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC). Butyl rubber gloves.
Skin protection - Other	Wear suitable protective clothing.
Respiratory protection	Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Various
Odour	Strong/Characteristic
Odour threshold	No data available
pH	No data available
Melting point	Not applicable.
Freezing Point	-48 °C
Initial boiling point	100 °C
Flash point	10 °C
Evaporation rate	Not applicable.
Flammability (solid, gas)	No data available
Upper Explosive Limit	12.5 %
Lower Explosive Limit	2.1 %
Vapour pressure	No data available
Vapour density	No data available
Relative density	0.979 (H ₂ O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	430 °C
Viscosity	200 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

10.1. Reactivity	
	See section 10.2 for further information.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	Oxidising agents.
10.4. Conditions to avoid	
	Heat, sparks and open flames.
10.5. Incompatible materials	
	Alkalis. Oxidising agents. Peroxides. Reducing agents. Sulphur oxides.
10.6. Hazardous decomposition products	
	Will not decompose if stored and used as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects	
Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	Irritating to eyes.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	No carcinogenic effects reported.
Reproductive toxicity	No observed effect level. No teratogenic effects reported.
Aspiration hazard	No Significant Hazard.

11.1.4. Toxicological Information

2-Ethylhexyl acrylate	Oral Rat LD50: 4,435mg/kg	Dermal Rabbit LD50: >5,000mg/kg
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg Dermal Rabbit LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg Inhalation Rat LC50/4 h: 29.8mg/kg
N,N-bis-(2-hydroxypropyl)-p-toluidine	Oral Rat LD50: 172mg/kg	

SECTION 12: Ecological information

12.1. Toxicity		
Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l
12.2. Persistence and degradability		
	Readily biodegradable. OECD 301C, 14D.	
12.3. Bioaccumulative potential		
	No observed effect level.	
Partition coefficient		
	Centrecoat MMA Clear Sealer - Base No data available	
12.4. Mobility in soil		
	Slightly soluble in water.	

Print date 2019-10-29

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

12.5. Results of PBT and vPvB assessment

PBT no. vPvB no.

12.6. Other adverse effects

No data is available on this product.

SECTION 13: Disposal considerations

General information

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal of packaging

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1866

14.2. UN proper shipping name

RESIN SOLUTION ((Methyl Methacrylate))

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group II

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

14.6. Special precautions for user

Not applicable.

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	Not applicable.
--	-----------------

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
--	--

15.2. Chemical safety assessment

	This product contains substances for which Chemical Safety Assessments are still required.
--	--

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 4 - Eye contact.
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 2: H300 - Fatal if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Maximum content of VOC	0 g/l.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in
--	--

Print date 2019-10-29

Centrecoat MMA Clear Sealer - Base

Revision 1

Revision date 2019-10-29

Further information

combination with any other materials or in any other process.