

Description

Centrecoat Premium Drive Sealer is a fast drying acrylic polymer based driveway sealer, designed to protect and enhance the appearance of tarmac driveways.

Centrecoat Premium Drive Sealer can be used to on new driveways or to refurbish existing driveways, giving an attractive satin finish that provides protection against staining and weather damage.

Colour and Finish

Transparent. Satin.

Preparation

Prior to application the surface must be clean, dry, stable and free from loose debris. A stiff broom should be used and a proprietary fungicidal wash to remove moss and algae. Oil and grease deposits should be removed with a good quality degreaser, rinsed with clean water and allowed to dry. Any repairs to the tarmac should be made with a proprietary cold cure tarmac and allowed to cure prior to application of Centrecoat Premium Drive Sealer.

New tarmac should be allowed to dry for 90 days prior to application.

Application

Centrecoat Premium Drive Sealer should be applied to a sound surface (see surface preparation above). Mix sealer thoroughly in the tin before pouring into a roller tray. Using a long pile roller, fully load the roller and apply the sealer, painting from the furthest point. The sealer should be stirred periodically in the tray.

Centrecoat Premium Drive Sealer may be overcoated after 4 hours, however on cooler, damp days this may be extended. Vehicles may be parked after the 2nd coat has cured for 4 hours. Centrecoat Premium Drive Sealer should be allowed to cure for 24 hours prior to heavy vehicular use and will continue to cure to optimum hardness over several days.

Centrecoat Premium Drive Sealer should only be applied in dry conditions and not be applied if it is forecast to rain within 12 to 24 hours. Application should be carried out in temperatures between 10°C and 30°C. Freshly applied product should be protected from frost.

Technical Data

- ▶ Acrylic Polymer Based
- ▶ Overcoatable: 4 hours
- ▶ Light Vehicle Ready: 4 hours
- ▶ Heavy Vehicle Ready: 24 hours
- ▶ Fully Cured: Several days

Coverage

6m² per litre per coat depending on the porosity of the existing substrate and the surface profile.

Clean Up

Once mixing and application are complete, tools can be cleaned with water and detergent.



PRODUCT DATA SHEET

Centrecoat Premium Drive Sealer

Storage

Store in closed containers above 5°C and under dry, well ventilated warehouse conditions, out of direct sunlight and away from naked flames or other sources of ignition. Protect from frost.

Shelf Life

At least 3 years if stored in original containers in appropriate conditions.

Packaging

Available in 20 Litres

