

Description

Centrecoat Strongcoat Primer is a two-pack solvent free, epoxy based primer for use with the Centrecoat Strongcoat and Griptop range of surface toppings.

Strongcoat Primer can be used where the RH of the substrate is greater than 75%. Apply by brush, roller or squeegee in one or two coats depending on the texture, porosity and evenness of the surface being primed.

Preparation

The surface must be clean, dry and free from dust, laitance, oils, paints or other forms of contamination. Grit blasting can be used to remove laitance and surface contamination. For treatment of surfaces containing expansion joints consult our Technical Department.

Mixing

Taking care to ensure that the bottom and sides are thoroughly scraped, transfer the entire contents of the Strongcoat Primer Hardener container into the Resin container and, using a paddle mixer attached to a slow-running electric drill, mix for approximately two minutes.

Important: Never mix Strongcoat Primer by hand as this could lead to areas of uncured material. Never leave the mixed Strongcoat Primer kit to stand for any length of time prior to application as this will considerably shorten its working time.

Application

Once mixing is complete, transfer the Strongcoat Primer to a roller tray and, using a medium-pile simulated sheepskin roller, apply it evenly over the surface. Before applying further coatings, ensure the Primer is not contaminated prior to being overlaid.

Technical Data

- ▶ Thickness: Approx 200 microns per coat
- ▶ Pot Life: 40 minutes at 20°C
- ▶ Overcoatable: Between 12 hours to 24 hours at 20°C

Coverage Rate

Approximately 4m²/kg at the specified coating thickness.

Important: This coverage figure is based on application to a smooth, dense surface. Coverage figures will vary according to the texture, porosity and evenness of the surface on which the Strongcoat Primer is being applied.

Clean Up

Once mixing and application are complete, tools can be cleaned with [Centrecoat MMA Tool Cleaner](#) or **Centrecoat Quickmast Solvent**.

Storage

Store at temperatures between 5°C and 30°C.

Shelf Life

Approximately 24 months if stored in unopened containers and under good conditions.

Packaging

Available in 5 and 10 Kg

Health & Safety

Consult the appropriate Material Safety Data Sheets prior to using Strongcoat Primer.

This Data Sheet is for general purposes only and may contain information which is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.